



Product Data Sheet

Cover Tape

Available in black or white



Product Information

Seal Trust™ Cover Tapes are cured EPDM cover rubber with specially formulated butyl mastic extruded together for typical roofing applications such as cover for most metal terminations including gravel-stops and drip edge, and extensively used for horizontal patching, seam repairs and seam overlays. This peel and stick product has long term heat and chemical resistance and gives Seal Trust Cover Tape the ability to remain flexible in harsh conditions. Surpassing the industry standards for tack and shear strength our cover tape products provide superior holding power for long life and high durability. Industry standard roofing membrane cleaners and primers must be used to clean the membrane before application. Used with EPDM, TPO, and some PVC roofing membranes.

Application Instructions:

Always clean and prime membrane using roofing industry standard products for tape applications such as Seal Trust™ F-Primer or Low VOC Tape Primer. Allow primer to dry before installing tapes. Cover Tape is not for use in flashing applications. Product is a peel and stick cured cover tape. Used for covering metal termination bars, drip edge, and/or all purpose bar in seam applications etc. Apply in primed area by peeling release paper off of 6-12 inches of tape. Stick the tape onto the membrane, while continuing to pull release paper off. Make sure you start on a straight line. Continue pulling release paper off as you move down the pre-primed area. Use sharp scissors for cutting the cover tape. Use metal seam roller with some force perpendicular to tape for proper adhesion.

Resistant to: Weather, water & water vapor, (5%) acidic or basic solutions

Effected by: Petroleum, grease, oil, solvents, vegetable oils, and animal fats

Product Storage: Store in warehouse without excessive heat. Do NOT store long term on roof.

Shelf Life: 1 year if stored between 60° and 80° F.

Physical Properties:

Color: Black or White

Odor: Slight Hydrocarbon

Volatile: % by Volume: None

Solids: 100%

Penetration: (ASTM D 217) : 100/130 mm

Adhesion: To most clean, dry substrates/surfaces

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.

User's Responsibility

This Product Information cannot cover all possible situations, which the user may experience during processing. Each aspect of your operations should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, express or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state and local laws and regulations remains the responsibility of the user.