



Product Data Sheet

Tape Primer

Available in Pints (24/cs) and 1 Gallon cans (6/cs)



Product Information

Contains Toluene CAS# 108-88-3, Hexane CAS# 110-54-3

VOC = 820 grams/liter DO NOT THIN

Tape Primer is a clear product specifically formulated as a primer for single ply membranes before the installation of any and all tape products such as seam, flashing and cover tapes along with pipe boots and patch disks. It is a clear product when dried allowing for use with white and black membranes. Tape Primer must be used prior to the installation of all tape products manufactured by Seal Trust™.

Application Instructions:

Always use Splice Wash on older, dirty membranes before the use of this product. Change rags frequently when cleaning dirty membranes. Tape Primer should be scrubbed into the membrane using scrub pads such as Scotch Brite pads. Allow to dry to the touch depending on temperature and humidity. Always use solvent resistant gloves when applying this product.

Physical Properties:

Color: Clear to neutral

Density (#/GAL.): 7.23#

Flash Point (F): -15F TCC

Solvent System: Aromatics and Aliphatics

Storage: May be stored outside if protected from water.

Viscosity (cps): #3 @ 20 rpm=200cps or less

% Solids: 4.8

Base: Synthetic elastomers, resin(s) and filler(s)

Clean-up Solvent: Mineral spirits, VMP naphtha or toluene

Packaging: Pints (24/cs), Gallons (6/cs)

Hazards: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire, flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the SDS.

Pint & 1 Gallon Freight Classification: UN1133, ADHESIVE, 3 PGII NMFC# 170060 CLASS 60

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.

User's Responsibility

This Product Information cannot cover all possible situations, which the user may experience during processing. Each aspect of your operations should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, express or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state and local laws and regulations remains the responsibility of the user.