



TPO and Rubber Roofing Products

QuickSeal Tapes Installation



QuickSeal Tapes are pressure sensitive adhesive tapes, which remain flexible even in cold temperatures. The fabric facer is designed to be coated to match the surrounding roofing surface. The white TPO facer makes QuickSeal tapes UV resistant.

QuickSeal Tapes may be used on metal roofs to strip in side laps, end laps, and other penetrations prior to the application of a coating system (with the use of QuickSeal Fabric Tape). QuickSeal Tape may also be used on EPDM, TPO, CSPE/Hypalon, CPE, SBS, APP modified, asphalt BURs, all metal roofs, tiles, aluminum, galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry and OSB. This product may be used to repair gutters, chimney flashings, and metal roofs on mobile homes and transport vehicles. QuickSeal Tape makes a watertight seal. Can be installed in temperatures down to 20°F (with EPDM Tape Primer).

Installation Instructions:

Install QuickSeal tape over repair area, remove liner gradually to prevent contamination of adhesive prior to application.

Rub or roll with pressure (preferably with a steel roller) to activate the bonding process QuickSeal tape may be applied to clean, dry surfaces from 20°F to 170°F. For low temperature application (below 40°F down to 20°F) treat surface with EPDM Tape Primer prior to application and maintain tape at room temperature (+60°F) prior to application. Apply roof coating to fabric surface of tape when using QuickSeal Fabric Tape.

EPDM QuickSeal Tapes

TPO QuickSeal Tapes



SealTrust Roofing
1175 E. Diamond Avenue
Evansville, IN 47711

Phone: 812.868.0790
Fax: 812.868.0789

email: cs@sealtrustroofing.com
www.sealtrustroofing.com