



TPO and Rubber Roofing Products

Cover Tape Installation



USAGE:

Seal Trust™ Cover Tapes are cured EPDM cover rubber with specially formulated butyl mastic extruded together for typical roofing applications such as cover for most metal terminations including gravel-stops and drip edge, and extensively used for horizontal patching, seam repairs and seam overlays. This peel and stick product has long term heat and chemical resistance and gives Seal Trust Cover Tape the ability to remain flexible in harsh conditions. Surpassing the industry standards for tack and shear strength,. Our Cover Tape products provide superior holding power for long life and high durability. Seal Trust Tack Back™ Primer, Tape Primer, or Low VOC Primer must be used to clean the membrane before application.

Directions:

Always clean and prime membrane using Seal Trust Tack Back™ Primer, Tape Primer, or Low VOC Primer. Allow primer to dry before installing tapes. Cover Tape is not for use in flashing applications. Apply in primed area by peeling release paper off of 6-12 inches of tape. Stick the tape onto the membrane, while continuing to pull release paper off. Make sure you start on a straight line. Continue pulling release paper off as you move down the pre-primed area. Use sharp scissors for cutting the cover tape. Use metal seam roller with some force perpendicular to tape for proper adhesion.



SealTrust Roofing
1175 E. Diamond Avenue
Evansville, IN 47711

Phone: 812.868.0790
Fax: 812.868.0789

email: cs@sealcorpUSA.com
www.sealtrustroofing.com