



Product Data Sheet



Water Cut-Off Mastic

Available in 10.5 oz. fiber caulk tubes

Product Information

Contents: Heptane 142-82-5

VOC = 176 grams/liter DO NOT THIN

Lap caulk available in 10.5 oz tubes for use in single ply membrane applications such as EPDM. Standard caulk gun is required for application. This caulk is meant to prevent water infiltration into seams and overlaps prior to the adhesive setting up. Usually 24-48 hours depending on temperature and humidity.

Hazards: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire, flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the MSDS.

Freight Classification: UN1133, ADHESIVE, 3 PGII NMFC# 170060 CLASS 60

Physical Properties:

Color: Gray

Viscosity (cps): 40# .104= 15-20 sec./20 gms. Sievers Rheometer

Density (#/GAL.): 10.5# ±.5

% Solids: 86

Flash Point (F): 16 F TCC

Base: Synthetic elastomers, resin(s) and filler(s)

Solvent System: Aliphatic

Clean-up Solvent: Mineral spirits, VMP naphtha, kerosene

Storage: May be stored outside if protected from water.

Packaging: 10.5 oz. fiber caulk tubes (25 tubes/ctn)

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.

User's Responsibility

This Product Information cannot cover all possible situations, which the user may experience during processing. Each aspect of your operations should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material.

Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, express or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state and local laws and regulations remains the responsibility of the user.

Manufactured for/Distributed by: SealCorpUSA, Inc. | (866) 868-0791 | (812)868-0790 | www.sealcorpusa.com

